


MINIMUM MEAN DIAMETER FOR CHAIN CABLE



COMMON LINK

Original chain diameter	Class society (IACS)	Original chain diameter	Class society (IACS)
mm	(12 %)	mm	(12 %)
12.50	11.00	64.00	56.32
14.00	12.32	66.00	58.08
16.00	14.08	68.00	59.84
17.50	15.40	70.00	61.60
19.00	16.72	73.00	64.24
20.50	18.04	76.00	66.88
22.00	19.36	78.00	68.64
24.00	21.12	81.00	71.28
26.00	22.88	84.00	73.92
28.00	26.64	87.00	76.56
30.00	26.40	90.00	79.20
32.00	28.16	92.00	80.96
34.00	29.92	95.00	83.60
36.00	31.68	97.00	85.36
38.00	33.44	98.00	86.24
40.00	35.20	100.00	88.00
42.00	36.96	102.00	89.76
44.00	38.72	105.00	92.40
46.00	40.48	107.00	94.16
48.00	42.24	108.00	95.04
50.00	44.00	111.00	97.68
52.00	45.76	114.00	100.32
54.00	47.52	117.00	102.96
56.00	49.28	120.00	105.60
58.00	51.04	122.00	107.36
60.00	52.80	124.00	109.12
62.00	54.56		

Note: The measurements in tables may vary between different models. Sotra Anchor & Chain AS can not be hold responsible for any deviate between tables and delivered equipment.