

STUDLESS CHAIN

STUDLESS CHAIN, GRADE 2 & GRADE 3

Diameter	Inside pitch	Weight per mtr	Breakload grade 2	Breakload grade 3	Length	Surface treatment
13 mm	45 × 18 mm	3,5 Kgs	98 kN		50 mtr	Tarred / Galv
16 mm	99 × 32 mm	4,5 Kgs	132,5 kN	184,8 kN	50 mtr	Tarred / Galv
19 mm	119 × 34 mm	6,3 Kgs	187 kN	260,6 kN	100 mtr	Tarred / Galv
22 mm	127 × 34 mm	8,6 Kgs	290 kN	349,4 kN	100 mtr	Tarred / Galv
24 mm	96 × 36 mm	11,5 Kgs	298,9 kN	415,8 kN	100 mtr	Tarred / Galv
26 mm	104 × 39 mm	14 Kgs	350,8 kN	488 kN	100 mtr	Tarred / Galv
28 mm	112 × 42 mm	16 Kgs	405,9 kN	566 kN	50/55 mtr	Tarred / Galv
30 mm	120 × 45 mm	18,5 Kgs	467,5 kN	649,8 kN	50/55 mtr	Tarred / Galv
32 mm	128 × 48 mm	20,5 Kgs	530,9 kN	739,3 kN	50/55 mtr	Tarred / Galv
36 mm	144 × 54 mm	26,5 Kgs	672,3 kN	935,7 kN	50/55 mtr	Tarred / Galv
40 mm	160 × 60 mm	32 Kgs	829,1 kN	1155,2 kN	50/55 mtr	Tarred / Galv
50 mm	200 × 75 mm	52 Kgs	1239,6 kN	1805 kN	50/55 mtr	Tarred / Galv
60 mm	240 × 90 mm	71 Kgs	1857,6 kN	2598 kN	50/55 mtr	Tarred / Galv

Note: Breakingload for hot dip galvanized chain will normally be reduced by approximate 15%.

STUDLESS CHAIN, GRADE 70

Diameter	Inside pitch	Weight per mtr	Breakload	Length	Surface treatment
10 mm	60 × 20 mm	1,75 Kgs	91,2 kN	100 mtr	Galvanized
13 mm	81 × 22 mm	2,9 Kgs	184,95 kN	50 mtr	Galvanized
16 mm	100 × 26 mm	4,3 Kgs	279,98 kN	50 mtr	Galvanized
19 mm	100 × 28 mm	6,5 Kgs	395,01 kN	50 mtr	Galvanized
22 mm	120 × 32 mm	8,5 Kgs	529,95 kN	50 mtr	Galvanized
25 mm	140 × 41 mm	11,2 Kgs	684,99 kN	50 mtr	Galvanized
28 mm	150 × 37 mm	14 Kgs	860,04 kN	50/100 mtr	Galvanized

Note: Breakingload for hot dip galvanized chain will normally be reduced by approximate 15%.
European made.

Note: The measurements in tables may vary between different models. Sotra Anchor & Chain AS can not be hold responsible for any deviate between tables and delivered equipment.